


**Everyvalve LTD**  
**Valve**  
Page 19

**ANGLE GLOBE VALVES (PNEUMATIC) SS & BRONZE**




A very useful Pneumatic Control valve for project and general Chemical & process industry applications. Normally Closed is Standard operation wns. Vacuum can be handled upon request by "Chevron" reversing seals. Compactness allows easy installation and also spares assy. Plastic actuators also supplied > Type 554 Seals : EPDM :- (Std) Seats:- PTFE Body :- SS or Bronze Temp Max : 130 Deg C. Pressure Range as shown = (Pr) Type 1 or 2 Metal Actuator>-----] . [ PP Actuator ]

	ACT 1	ACT 1	ACT 2	ACT 2	-	-
Type=>M2	BRONZE	SS316	BRONZE	SS316	BRONZE	SS316
Sizes (Pr)>	19M1514A	19M1514B	(Pr)19M2514A	19M2514B	19M554A	19M554B
1/2" (35)>	£154.00	£241.00	-	-	£90.00	£183.00
3/4" (20)>	£165.00	£263.00	-	-	£96.00	£195.00
1" (10)>	£178.00	£298.00	-	-	£106.00	£222.00
1.25" (7)>	£184.00	£353.00	(10)>£294.00	£478.00	£124.00	£280.00
1.5" (4)>	£202.00	£408.00	(10)>£316.00	£538.00	£134.00	£335.00
2" (3)>	£240.00	£495.00	(10)>£355.00	£627.00	£144.00	£407.00
2.5"	-	-	( 7>£490.00	£1280.00	-	-
3"	-	-	( 5>£543.00	-	-	-

Right angled versions are available up 150mm in size (Flanged) Accessories are supplied as extra-> Stroke Limiters, Indicators potentiometric control etc. "554" pressures are 10 Bar over seat. See [page 15](#) for solenoid control valves 15ML377.

**SWING FLAP VALVES (Wafer IN SS 316 & CS)**




Non return valve for fitting between PN flanges in STEEL pipe- work on a horizontal or vertical plane. Maximum pressure is 16 bars and flows to 4 M / second. Seats are soft FPM with other options of construction. Pulsing service must be avoided. Use bolt torque data shown for "Spring Check Valve". Uses for water, air, chemicals & some acids (SS). Temps to 150°C (Subject to Seals)

Size	Bore	O.D	Thick	Weight	£/Each		£/Each	
					C.S.-	REFERENCE	S.S.-	REFERENCE
11/2"	40	86	15	1	£ 65.00	19M31C15	£ 64.00	19M31B15
2"	31mm	97	16	1	£ 66.30	19M31C20	£ 66.00	19M31B20
2.5"	37mm	110	16	1	£ 75.08	19M31C25	£ 85.00	19M31B25
3"	46mm	129	23	2	£ 95.00	19M31C30	£ 104.00	19M31B30
4"	66mm	160	23	4	£ 115.00	19M31C40	£ 145.00	19M31B40
5"	91mm	193	23	5	£ 145.00	19M31C50	£ 218.00	19M31B50
6"	116mm	216	23	6	£ 160.00	19M31C60	£ 280.00	19M31B60
8"	145mm	273	23	14	£ 210.00	19M31C80	£ 440.00	19M31B80
10"	191mm	330	30	19	£ 395.00	19M31C81	£ 640.00	19M31B81
12"	217mm	380	30	32	£ 470.00	19M31C82	£ 918.00	19M31B82
14"	263mm	446	43	40	£ 795.00	19M31C83	POA	19M31B83
16"	305mm	498	46	51	POA	19M31C84	POA	19M31B84

C.S. Bodied versions are zinc plated + Nitrile seal to BS7773 4360/43a S.S. Bodied versions are in grade 316 + FPM seal. Gunmetal Versions also available (add 10% to SS prices) BS1400 Dual Plate versions = See [page 23](#).

**SPRING CHECK VALVES (Wafer Type) IN SS316 & CS**



Non Return Valve for fitting between PN40 flanges in STEEL pipe work only, at any angle. The spring is standard set at 200mm water gauge cracking but other loadings are possible. Max pressure usable is 48 bars & Max temp is 150C. Soft seals are extra in "FPM" or NEOPRENE. Valve Fits between 4504 BS 10 and 1560 flanges. Other body materials available. Applications for water, chemicals & air. Avoid shock use.

Prices:- (Soft FPM seal +15%)

Size	Metric Bore	Thick.	O.D.	Bolt	Torque.	£/Each		£/Each	
						C.S.	REFERENCE	S.S.	REFERENCE
1/2"	12mm	16mm	x 45	3.5	kg/m	46.20	19M4005	56.00	19M4105
3/4"	20mm	19mm	x 55	3.5	kg/m	60.90	19M4007	66.00	19M4107
1"	25mm	22mm	x 65	3.5	kg/m	65.00	19M4010	80.00	19M4110
1.25"	32mm	28mm	x 76	4.0	kg/m	84.00	19M4012	92.00	19M4112
1.5"	40mm	32mm	x 86	5.0	kg/m	90.00	19M4015	97.00	19M4115
2"	50mm	40mm	x 98	6.0	kg/m	110.00	19M4020	120.00	19M4120
2.25"	65mm	50mm	x 111	6.5	kg/m	130.00	19M4025	144.00	19M4125
3"	75mm	50mm	x 130	7.0	kg/m	138.00	19M4030	148.00	19M4130
4"	100mm	105mm	x 154	8.0	kg/m	174.00	19M4040	192.00	19M4140
6"	160mm	140mm	x 272	8.0	kg/m	POA	19M4060	425.00	19M4160

All information given as a guide only. Suitability must be established before application of products always.

PLEASE NOTE : Prices subject to change without prior notice.